



**KLEENTEK**

a CLARCOR company

# Oil Conditioning Systems

## Specifications

<b>Flow Rate:</b>	30 gph (114 lph)
<b>Max. Temp.:</b>	140°F
<b>Operating Temp.:</b>	32°F-120°F
<b>Max. H<sub>2</sub>O Content:</b>	500 ppm (options available for >500 ppm)
<b>Electrical Rating:</b>	NEMA 4
<b>Weight:</b>	115 lbs (52.3 kg)
<b>Weight (operating):</b>	140 lbs (63.6 kg)
<b>Power Supply:</b>	115 V/1PH/60Hz 640 Watts (790 Watts with heater kit)
<b>Voltage:</b>	10-12 KVAC
<b>Voltage Cut-Off:</b>	3 KVAC
<b>Cartridge/Set:</b>	1
<b>Collector Part #:</b>	60-0472
<b>Seals:</b>	Viton
<b>Dimensions:</b>	w x l x h 13.75 in x 21.50 in x 21.50 in 34.90 cm x 54.60 cm x 54.6 cm

### Replace Collectors:

2,000-4,000 + hours for first set, then 8,000 hours (1 yr.) after initial oil cleanup (less for high load applications).




**Change at least once a year for best performance.**

## Model DOC-N10

Designed for volumes less than 1,050 gallons, Model N10 electrostatically cleans lubricants of contaminants while eliminating the need for mechanical filters. It circulates oil at a very low velocity, removing submicron particles and large contaminants from hydraulic fluids and lubricating oils.



## Features

-  NEMA 4 rating
-  Good for oil reservoirs to 1,050 gallons
-  Flow rate of 30 gph